

**MATERIAL SAFETY DATA SHEET**

**RTV 8512 (SIL-COAT)  
(CLEAR)**

**1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY**

Silco Incorporated  
7561 Tyler Blvd.  
Unit # 6  
Mentor, Oh 44060

Phone: (440)-975-8886  
Fax: (440)-975-8887

Revision Date: 10/01/06

General Description: Silicone elastomer  
Physical Form: Viscous Liquid  
Color: Colorless  
Odor: Acetic acid odor

NFPA PROFILE: Health - 2 Flammability - 2 Instability/Reactivity - 0

Note: NFPA = National Fire Protection Association

**2. OSHA HAZARDOUS COMPONENTS**

CAS Number	Wt %	Component Name
4253-34-3	1.0 – 5.0	Methyltriacetoxysilane
17689-77-9	3.0 – 7.0	Ethyltriacetoxysilane
541-02-6	<1.0	Decamethylcyclopentasiloxane
556-67-2	<1.0	Octamethylcyclotetrasiloxane
108-24-7	<= 0.1	Acetic anhydride
64-19-7	<= 0.1	Acetic acid

The above components are hazardous as defined in 29 CFR 1910.1200.

**3. EFFECTS OF OVEREXPOSURE**

Accute Effects:

Eye: Direct contact may cause moderate irritation.  
Skin: May cause moderate irritation  
Inhalation: Irritates respiratory passages very slightly  
Oral: Low ingestion hazard in normal use.

#### Prolonged / Repeated Exposure Effects

Skin: No Known applicable information.  
Inhalation: No Known applicable information.  
Oral: No Known applicable information.

#### Signs and Symptoms of Overexposure

No Known applicable information.

#### Medical Conditions Aggravated by Exposure

No Known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and / or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

#### **4. FIRST AID MEASURES**

Eye: Immediately flush with water for 15 minutes. Get medical attention.  
Skin: Remove from skin and wash thoroughly with soap and water or waterless cleanser.  
Get medical attention if irritation or other ill effects develop or persist.  
Inhalation: No first aid should be needed.  
Oral: No first aid is needed.  
Comments: Treat according to person's condition and specifics of exposure.

#### **5. FIRE FIGHTING MEASURES**

Flash Point: 188.6 F / 87 C (Closed Cup)  
Autoignition Temperature: Not determined  
Flammability Limits in Air: Not determined  
Extinguishing Media: On large scale fires use dry chemical foam or water spray. On small fires use carbon dioxide (CO<sub>2</sub>), dry chemical or water spray. Water can be used to cool fire exposed containers.  
Fire Fighting Measures: Self contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.  
Usual Fire Hazards: None.

#### Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Silicon dioxide. Formaldehyde.

## 6. ACCIDENTAL RELEASE MEASURES

Containment / Clean up: Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in section 5 and 8. Wipe up and contain for salvage or disposal. Clean area as appropriate since some silicone materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state, and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state, and local laws and regulations are applicable. Section 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See section 8 for Personal Protective Equipment for Spills. Call Silco Incorporated at (440)-975-8886, if additional information is required.

## 7. HANDLING AND STORAGE

Use with adequate ventilation. Product evolves acetic acid (HOAc) when exposed to water or humid air. Provide ventilation during use to control HOAc within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact.

Static electricity will accumulate and may ignite vapors. Prevent possible fire hazard by bonding and grounding or inert gas purge. Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water, moisture, heat, sparks and flame.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Component Exposure Limits

CAS Number	Component Name	Exposure Limits
4253-34-3	Methyltriacetoxysilane	See acetic acid comments
17689-77-9	Ethyltriacetoxysilane	See acetic acid comments

Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm. STEL 15 ppm.

### Engineering Controls

Local Ventilation: Recommended  
General Ventilation: Recommended

### Personal Protective Equipment for Routine Handling

Eyes: Use proper protection – safety glasses as a minimum  
Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Silver Shield ® 4H®.  
Inhalation: No respiratory protection should be needed.  
Suitable Respirator: None should be needed.

#### Personal Protective Equipment for Spills.

Eyes: Use proper protection – safety glasses as a minimum.  
Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Inhalation / Suitable Respirator: No respiratory protection needed.

Precautionary Measures: Avoid eye contact. Avoid skin contact. Use reasonable care.

Comments: Product evolves acetic acid (HOAc) when exposed to water or humid air. Provide ventilation during use to control HOAc within exposure guidelines or use respiratory protection.

When heated to temperatures above 150 degrees C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin, and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for Formaldehyde.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol / spray applications may require added precautions.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Viscous Liquid
Color:	Colorless
Odor:	Acetic Acid odor
Specific Gravity @ 25 C:	1.03
Viscosity:	350 cSt
Freezing / Melting Point:	Not determined
Boiling Point:	> 35 C / 95 F
Vapor Pressure @ 25C:	Not determined
Solubility in Water:	Not determined
PH:	Not determined
Volatile Content:	< 5%

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

## 10. STABILITY AND REACTIVITY

Chemical Stability: Stable.  
Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid;                   None  
Material to Avoid:                   Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors to form as described in section 8.

## 11. TOXICOLOGICAL INFORMATION

### Special Hazard Information on Components

No known applicable information.

## 12. ECOLOGICAL INFORMATION

### Environmental Fate and Distribution

Complete information is not yet available.

### Environmental Effects

Complete information is not yet available.

### Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available

#### Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC 50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<= 100	> 100 and <= 2000	>2000

- This table is adapted from “Environmental Toxicology and Risk Assessment”. ASTM STP 1179, p34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

## 13. DISPOSAL CONSIDERATIONS

### RCRA Hazard Class (40 – CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal.

Call Silco Incorporated at (440)-975-8886, if additional information is required.

#### 14. TRANSPORT INFORMATION

DOT Road Shipment Information (49 CFR 172.101)

Proper Shipping Name:	Combustible Liquid, N.O.S.
Hazard Technical Name:	Acetoxysilane
Hazard Class:	Combustible Liquid
UN / NA Number:	NA 1993
Packing Group:	III
Remarks:	Above applies only to containers over 119 gallons or 450 liters.

Ocean shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Call Silco at (440)-975-8886, if additional information is required.

#### 15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of chemical Substances.

EPA SARA Title III Chemical Listings

Section 302 Extremely Hazardous Substances:	None
Section 304 CERCLA Hazardous Substances:	None
Section 312 Hazard Class:	

Acute:	Yes
Chronic:	No
Fire:	Yes
Pressure:	No
Reactive:	No

Section 313 Toxic Chemicals: None present or none present in regulated quantities.

Supplemental State Compliance Information

California

Warning: this product contains the following chemicals listed by the state of California under the safe Drinking Water and toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

Massachusetts

No ingredient regulated by MA Right-to-Know Law present.

New Jersey

CAS Number	Wt%	Component Name
70131-67-8	> 60.0	Dimethyl siloxane, hydroxy terminated
112945-52-5	7.0 – 13.0	Amorphous fumed silica
4253-34-3	1.0 – 5.0	Methyltriacetoxysilane
17689-77-9	3.0 – 7.0	Ethyltriacetoxysilane

Pennsylvania

CAS Number	Wt%	Component Name
70131-67-8	> 60.0	Dimehtyl siloxane, hydroxy-terminated
112945-52-5	7.0 – 13.0	Amorphous fumed silica
17689-77-9	3.0 – 7.0	Ethyltriacetoxysilane

**16. OTHER INFORMATION**

Prepared By: Silco Incorporated

These data are offered in good faith as typical values and not as product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

**\*\*\*\* END OF MSDS \*\*\*\***